

179.00 EUR
incl. 19% VAT, plus shipping

Support: Specifications [EN]

- Processor N2600 / N2800 + NM10 Chipset
- 1 * DDR3 800MHz Single CH SO-DIMM up to 2GB
- Support DirectX 9 Graphics up to 640MHz
- Support 1 * Serial ATAII (3Gb/s) & 2 * Serial ATAIII (6Gb/s) Devices
- Integrated Realtek ALC662 HD Audio CODEC with 6-CH
- Integrated 18-bits Single CH & 24-bits Dual CH LVDS
- Supports 1 * Realtek RT8111EVL Gigabit LAN
- Supports ACPI S3 Function
- Support CPU Smart FAN
- Support Watch dog Technology
- Mini-ITX Form Factor(17cm x 17cm)
- Slim & Fanless design, within 2cm height

CPU	INTEL® Cedar Trail-M Processor N2600(1.6GHz) / N2800 (1.86GHz)
Chipset	INTEL®NM10 Express chipset
Memory	1 * DDR3 800MHz Single CH SO-DIMM up to 2GB
Expansion Slots	1 * PCI slot
	1 * MINI PCI-E
Storage	1 * Serial ATAII (3Gb/s) & 2 * Serial ATAIII (6Gb/s) connectors
	1 * CFast card socket
Audio	Realtek ALC662 6-Channel HD Audio
Ethernet LAN	1 * RTL8111E PCI-EVL Gigabit LAN
LVDS	1 * 18-bits Single CH & 1 * 24-bits Dual CH LVDS connectors

- **USB**
  - Embedded 7 * USB 2.0/1.1
  -
- **Special Features**
  - Support ACPI S3
  - Support CPU Smart FAN
  - Support Watch Dog
- **Rear Panel I / O**
  - 3 * USB 2.0/1.1 ports
  - 1 * RJ-45 port
  - 1 * HDMI port
  - 1 * COM port
  - Line-out connector
  - 1 * 12V DC in
- **Internal I / O**
  - 2 * USB 2.0/1.1 headers for 4 USB 2.0 ports
  - 1 * KB/MS headers
  - 1 * VGA header
  - NB / Chassis Fan connectors;
  - 2 * LVDS headers & 1 * GPIO header & 1 Parallel headers
  - 3 * COM headers (COM4 for RS232/422/485)
  - 1 * AUDIO header
  - 1 * chassis intrusion header
- **BIOS**
  - AMI 16MB DIP Flash ROM
- **Form Factor**
  - Mini ITX Form Factor (170mm x 170mm)
- **Functional**
  - ATM, Security, Digital Signage, POS, General Application, Transportation
- **Certificate**
  - CE, FCC, RoHS
- **Temperature**
  - Operating within 0~60 centigrade
  - Storage within -20-85 centigrade

Product Accessories
- 3x COM cable
- Manual
- CD
- 2x SATA cable
- I/O shield
- 1x power cable