

999.00 EUR
incl. 19% VAT, plus shipping

- INTEL® LGA 1150 Processor + B85 Chipset
- Support 2 * DDR3 1600/1333MHz Dual CH up to 16GB
- Support DirectX 9 Graphics
- Support 2 * Serial ATAIII (6Gb/s) Devices
- Integrated Realtek ALC662 HD Audio CODEC with 6-CH
- 1 * 24 bits Dual Channel LVDS header
- Supports 1 * Intel i217LM Gigabit LAN
- Support 6 * COM ports (COM1 support RS232/422/485)
- Support Windows 8
- Support Watch dog Technology
- Provides AT mode power
- Support CPU Smart FAN
- Compliance with ErP standard
- Mini-ITX Form Factor (170mm x 170mm)

CPU	INTEL® LGA1150
Chipset	INTEL® B85 chipset
Memory	2 * DDR3 1600/1333MHz Dual CH SO-DIMM up to 16GB
Expansion Slots	1 * PCI –E x 16 slot

• **Storage**	• 2 * Serial ATA3 6Gb/s connectors • 1 * mSATA full size slot (Share W/Mini PCI-E slot)
• **Audio**	• Realtek ALC662 6-Channel HD Audio
• **Ethernet LAN**	• 1 * INI217LM PCI-E Gigabit LAN
• **LVDS**	• Onboard 1 * 24-bits Dual channel connector
• **USB**	• Embedded 6 * USB 2.0/1.1 / 2* USB 3.0
• **Special Features**	• Support ACPI S3 • Support CPU Smart FAN • Support Watch Dog
• **Rear Panel I/O**	• 2 * USB 2.0/1.1 ports • 2 * USB 3.0 ports • 1 * RJ-45 port • 3 * Audio I/O ports (Line-in, MIC and Line-out) • 3 * VGA ports • 3 * COM ports (COM1 for RS232/422/485)
• **Internal I/O**	• 2 * USB 2.0/1.1 headers for 4 USB 2.0 ports • 3 * COM ports header • 2 * NB / Chassis Fan connectors • 1 * LVDS headers /1 * Inverter headers • 1 * AUDIO header • 1 * HDMI-SPDIF header • 1 * PS/2 header • 1 * TPM header • 1 * GPIO header • 1 * AT mode selectable header • 1 * Chassis Intrusion
• **BIOS**	• AMI 64MB UEFI DIP Flash ROM
• **Functional**	• POS Machine
• **Packing**	• Color Box Dimension■200(W) x 200(D) x 70(H)mm
• **Certificate**	• CE, FCC, RoHS
• **Temperature**	• Operating within 0~40 centigrade • Storage within -20-85 centigrade
• **Form Factor**	• Mini ITX Form Factor(17cmx17cm)