



598.00 EUR
incl. 19% VAT, plus [shipping](#)



- Intel® LGA1151 Socket Core i3,i5,i7 & Pentium Processors(max.65W)
- Support DDR4-2133Mhz, 2* SO-DIMM slot, up to 32GB memory
- 2* USB2.0, 4* USB3.0, 1* HDMI, 1* DP, 2* RJ45, 1* MIC, 1* Line in, 1* Line out
- M/B Form Factor : Mini ITX (170x170mm)
- 1U 200W FLEX Power

| | |
|-----------------|--|
| MB Model | – JNF693-H110 / Mini ITX – JNF694L-4200 / Mini ITX |
| Part No. | – HBJC150F693-H110-B (non-WIFI) – HBJC150F693W-H110-B (WIFI) |
| BIOS | – AMI 64MB SMT Flash ROMM |
| CPU/Chipset | – Intel® LGA1151 Socket Core i3,i5,i7 & Pentium Processors |
| Memory | – 2 * DDR4-2133 up to 32GB |
| Storage | – 2 * 2.5" or 1 * 3.5" SATA3 6Gb/s internal drive bay – 1 * M.2_SSD (M key-2242/2260) |
| Network | – 2 * Realtek® 8111H Gigabit LAN – 1 * Full-size mini-PCIE slot (802.11 b/g/n + BT 4.0 installed in WIFI model / Optional) |
| Rear Panel I/O | – 4 * USB 3.0 – 1 * HDMI (Max Resolution : 3840x2160@24Hz) – 1 * DP (Max Resolution : 4096x2304@60Hz) – 2 * RJ45 – 1 * Mic, 1 * Line in, 1 * Line-out (Realtek ALC662) – 4 * RS232 – 1 * AC-in |
| Front Panel I/O | – 1 * Power button, 1 * Reset button – 1 * Power LED, 1 * HDD LED – 2 * USB 2.0 |
| Power Source | – 1U 200W FLEX POWER – AC 90~240V input |
| Compliance | – CE, FCC, LVDS, RoHS |
| Temperature | – Operating Temperature: 0 ~ 50° C – Storage Temperature: -10 ~ 70° C |
| Dimensions | – 430 (W) x 252 (D) x 44 (H) mm |
| Packing | – Net Weight: 3.5KG – Gross Weight: 4.5KG – Color Box dimension: 560 (W) * 400 (D) * 140 (H) mm |
| OS Support | – 32/64 bit versions of Windows 7, Windows 8.1, Windows 10, Linux |

| | |
|----------|---------------------------|
| Warranty | - 2 Year limited warranty |
|----------|---------------------------|