**Jetway JBC143F694W-420B (Intel Apollo Lake)**
[http://www.cartft.com/catalog/il/2669]

498.00 EUR
incl. 19% VAT, plus shipping

- Intel® Apollo Lake SoC Processor
- 1 * DDR3L SODIMM Up to 8GB
- 4 * COM, 4 * USB3.0, 1 * HDMI, 1 * DP, 1 * RJ45, 1* MIC, 1 * Line-in, 1 * Line-out
- M/B Form Factor : Mini ITX (170x170mm)
- 1U 200W FLEX Power

| | |
|---|---|
| MB Model | – JNF694L-3350 / Mini ITX<br>– JNF694L-4200 / Mini ITX |
| Part No. | – HBJC143F694-335B (non-WIFI) / HBJC143F694W-335B (WIFI)<br>– HBJC143F694-420B (non-WIFI) / HBJC143F694W-420B (WIFI) |
| BIOS | – AMI Flash ROM |
| CPU/Chipset | – INTEL® Apollo Lake SoC Processor |
| Memory | – 1 * DDR3L-1866 MHz up to 8 GB |
| Storage | – 1 * 2.5” SATA 6Gb/s_ internal drive bay<br>– 1 * M.2_SSD (M key-2242/2260) |
| Network | – 1 * Realtek® 8111H Gigabit LAN<br>– 1 * Full-size mini-PCIE slot ( 802.11 b/g/n + BT 4.0 installed in WIFI model / Optional ) |
| Rear Panel I/O | – 4 * USB 3.0<br>– 1 * HDMI 1.4 (Max Resolution : 3840×2160@24Hz)<br>– 1 * DP (Max Resolution : 4096×2160@60Hz)<br>– 1 * RJ45<br>– 1 * MIC, 1 * Line-in , 1 * Line-out (Realtek ALC662)<br>– 4 * RS232<br>– 1 * AC-in CON |
| Front Panel I/O | – 1 * Power button, 1 * Reset button<br>– 1 * Power LED, 1 * HDD LED<br>– 2 * USB 2.0 |
| Power Source | – 1U 200W FLEX POWER<br>– AC 90~240V input |
| Compliance | – CE, FCC, RoHS |
| Temperature | – Operating Temperature: 0 ~ 50° C<br>– Storage Temperature: -10 ~ 70° C |
| Dimensions | – 330 (W) x 192 (D) x 44 (H) mm |
| Packing | – Net Weight: 3.5KG<br>– Gross Weight: 4.5KG<br>– Color Box dimension: 406 (W) * 359 (D) * 148 (H) mm |
| OS Support | – Windows 10 64bit, latest Linux kernel |

| | |
|---|---|
| Warranty | – 2 Year limited warranty |