



379.00 EUR  
incl. 19% VAT, plus [shipping](#)

The JETWAY HBJC420U691 Series adopts the Intel® Apollo Lake SoC processor. The board has one 204-pin DDR3L 1866MHz SODIMM up to 8GB memory. JNU691 Series equipped with 2 \* HDMI and 1 \* VGA for IoT applications. Intel® Apollo Lake SoC processor support AES NI which is a new hardware encryption instructions to improves on the AES algorithm and accelerates the encryption of data. JNU691 also support TPM feature to secure customers' data.

In addition, it offers 4 \* USB3.0 ports which can connect different peripherals, e.g. camera and sensor. It is flexible expansion via Mini PCIe slot, SIM card holder, and one RS232 port. An internal Mini-SATA slot provide storage selection. In addition, HBJC420U691 size is 129 \* 109.4 \* 34 mm and is a SubCompact, powerful and energy efficient NUC form factor fanless box system with reliable performance.

- Intel® Apollo Lake N3350/J3455 SoC Processor
- 1\* 204-pin DDR3L 1866MHz SODIMM Up to 8 GB
- 2\* 10/100/1000 Base-TX Ethernet Ports
- Support Intel AES NI and TPM2.0 to secure customers' data
- 4\* Ext USB3.0, 1\* Line-Out/MIC, 2\* HDMI, 1\* VGA
- 1\* full size mSATA, 1\* half size Mini PCIe Slot, 1\* SIM card holder
- 12V DC-in power

|             |   |
|-------------|---|
| MB Model    | - JNU691-3350 (NUC)<br>- JNU691-3455 (NUC)  |
| Part No.    | - HBJC420U691-335B / HBJC420U691-345B (non-WIFI)<br>- HBJC420U691W-335B / HBJC420U691W-345B (WIFI)  |
| BIOS        | - AMI Flash ROM   |
| CPU/Chipset | - Intel Apollo Lake N3350 Dual Core SoC Processor (up to 2.4GHz, 6W)<br>- Intel Apollo Lake J3455 Quad Core SoC Processor (up to 2.3GHz, 10W) |
| Memory      | - 1 * 204-pin SO-DIMM DDR3L-1866 (Max. 8GB)   |
| Support TPM | - TPM 2.0 on board  |
| Storage     | - 1 * Full-size mSATA/mini-PCI Express shared slot  |
| Network     | - 2 * Realtek RTL8111H GbE<br>- 1 * Half-size mini-PCIE slot (for WIFI model)<br>- 1 * SIM Card Slot  |

|                 |   |
|-----------------|---|
| Rear Panel I/O  | <ul style="list-style-type: none"> <li>- 2 * USB 3.0 ports</li> <li>- 2 * HDMI (max. 3840x2160@30Hz resolution)</li> <li>- 2 * RJ45</li> <li>- 1 * Audio (Line-out, Mic-in)</li> <li>- 2 * Antenna holes</li> <li>- 1 * DC-In jack</li> </ul> |
| Front Panel I/O | <ul style="list-style-type: none"> <li>- 1 * Power button + Power LED</li> <li>- 1 * COM(RS232/RS422/RS485)</li> <li>- 2 * USB 3.0 ports</li> <li>- 1 * VGA (max. 1920x1200@60Hz resolution)</li> </ul>                                       |
| Power Source    | <ul style="list-style-type: none"> <li>- AC-DC Adapter / DC12V-3.3A-40W</li> <li>- AC 90~240V input</li> </ul>  |
| Compliance      | <ul style="list-style-type: none"> <li>- CE, FCC, RoHS, ErP Ready</li> </ul>  |
| Temperature     | <ul style="list-style-type: none"> <li>- Operating Temperature: 0 ~ 50° C</li> <li>- Storage Temperature: -20 ~ 80° C</li> </ul>  |
| Dimensions      | <ul style="list-style-type: none"> <li>- 129 (W) x 109.4 (D) x 34 (H) mm</li> </ul>   |
| Packing         | <ul style="list-style-type: none"> <li>- Net Weight: 0.6KG</li> <li>- Gross Weight: 1.4KG</li> <li>- Color Box dimension: 158 (W) * 167 (D) * 123.6 (H) mm</li> </ul>   |
| OS Support      | <ul style="list-style-type: none"> <li>- Windows 10, Linux</li> </ul>   |
| Warranty        | <ul style="list-style-type: none"> <li>- 2 Year limited warranty</li> </ul>   |