



79.95 EUR
incl. 19% VAT, plus [shipping](#)



- Applied Solid Capacitor for CPU VRM to ensure a longer lifespan for system
- ECS Durathon Technology ensure the stability, reliability and performance of system.
- Dual Display design for multiple output support
- Integrated Printer (LPT) port / header to expand functionality
- Microsoft Windows 8 Certified
- Intel® VRD 12 Ready
- Supports DirectX® 11 to enhance graphical performance
- Supports HDMI 1.4a Technology (resolution up to 1920X1200) and HDCP function
- Free Bundle: CyberLink Media Suite

Supports Intel® CNVi

CPU

Onboard Intel® Bay Trail
processors
On-Board CPU Intel® Bay
Trail J1900 processor
VRD 12.0
Solid Capacitor for CPU
side
Supports Intel®
Hyper-Threading
Technology

| | |
|-----------------------|--|
| GRAPHICS | Supports DirectX® 11 Supports Full HD 1080P Blu-ray / HD-DVD Playback Single-channel DDR3 |
| MEMORY | Memory architecture 1 X DDR3 SO-DIMM socket Support up to 8 GB |
| EXPANSION SLOT | 1 X PCI Express X 1 Gen 2.0slot(s) 1 X Mini PCI Express X1 slot(s) for Wi-Fi /Bluetooth modules |
| Storage | 2 X Serial ATAIII 3Gb/s |
| Audio | 6-Channel HD audio CODEC Realtek ALC662 Realtek ALC662 6-channel High Definition audio CODEC Meets performance requirements for Microsoft WLP 3.08 Vista premium and mobile PCs Six channel DAC supports 16/20/24-bit PCM format for 5.1 channel audio solution Emulation of 26 sound environments to enhance gaming experience Voice Cancellation and Key Shifting in Karaoke mode Compatible with Direct Sound 3D™, A3D™, I3DL2 |
| LAN | Realtek RTL8111G Gigabit Fast Ethernet Controller |
| USB | 1 X USB3.1 Gen1 port(s) up to 5Gb/s 6 X USB2.0 port(s) Up to 480 Mb/s (Back Panel 4 port(s), Onboard 2 port(s)) 1 X PS/2 Keyboard & PS/2 mouse connectors 1 X Audio port (Line Out/Line In/Mic In) |
| REAR PANEL I/O | 1 X RJ-45 port 1 X HDMI port(s) 1 X D-Sub (VGA) port(s) 1 X USB3.1 Gen1 port(s) 4 X USB2.0 port(s) |

| | |
|-------------------------------------|---|
| | 1 X 4-pin CPU_FAN connector with smart fan |
| | 1 X 4-pin SYS_FAN connector with smart fan |
| | 1 X Front Panel MIC/Speaker out header |
| | 1 X Front Panel switch/LED header |
| CONNECTORS & HEADERS | 1 X USB 2.0 header (Support additional 2 USB ports) |
| | 2 X SATA II 3Gb/s connector(s) |
| | 1 X CLR_CMOS header |
| | 2 X Serial port header (COM) |
| | 1 X Parallel port header (LPT) |
| | 1 X LVDS connector (optional) |
| | AMI BIOS with 8 MB SPI Flash ROM |
| | Supports ACPI 5.0 & DMI |
| SYSTEM BIOS | Dual Display Plug and Play, STR (S3) / STD (S4) , Hardware monitor, Multi Boot |
| | Multi-Language BIOS |
| | Audio, LAN, can be disabled in BIOS |
| | Dual-Monitor function |
| FORM FACTOR | Mini ITX Form Factor 170*170 |
| | Windows 7 64-bit |
| OS Support | Windows 8.1 32-bit |
| | Windows 8.1 64-bit |
| | Windows 10 64-bit |
| | Windows 10 32-bit |
| Certifications | CE/FCC Certification |
| | ErP/EuP Certification |
| | WHQL Certification |
| | WHCK Certification |