


999.00 EUR
incl. 19% VAT, plus [shipping](#)



- Applied Solid Capacitor for CPU VRM to ensure a longer lifespan for system
 - ECS Durathon Technology ensure the stability, reliability and performance of system.
 - Dual Display design for multiple output support
 - Integrated Printer (LPT) port / header to expand functionality
 - Microsoft Windows 8 Certified
 - Intel® VRD 12 Ready
 - Supports DirectX® 11 to enhance graphical performance
 - Supports HDMI 1.4a Technology (resolution up to 1920X1200) and HDCP function
 - Free Bundle: CyberLink Media Suite
- Supports Intel® CNVi

CPU	Onboard Intel® Bay Trail processors On-Board CPU Intel® Bay Trail J1900 processor VRD 12.0 Solid Capacitor for CPU side Supports Intel® Hyper-Threading Technology Supports DirectX® 11
GRAPHICS	Supports Full HD 1080P Blu-ray / HD-DVD Playback Single-channel DDR3 Memory architecture
MEMORY	1 X DDR3 SO-DIMM socket Support up to 8 GB
EXPANSION SLOT	1 X Mini PCI Express X1 slot(s) for Wi-Fi /Bluetooth modules
Storage	2 X Serial ATAIII 3Gb/s 6-Channel HD audio CODEC Realtek ALC662 Realtek ALC662 6-channel High Definition audio CODEC Meets performance requirements for Microsoft WLP 3.08 Vista premium and mobile PCs
Audio	Six channel DAC supports 16/20/24-bit PCM format for 5.1 channel audio solution Emulation of 26 sound environments to enhance gaming experience Voice Cancellation and Key Shifting in Karaoke mode Compatible with Direct Sound 3D™, A3D™, I3DL2
LAN	Realtek RTL8111G Gigabit Fast Ethernet Controller
USB	1 X USB3.1 Gen1 port(s) up to 5Gb/s 8 X USB2.0 port(s) Up to 480 Mb/s (Back Panel 4 port(s), Onboard 4 port(s))

REAR PANEL I/O	1 X PS/2 Keyboard & PS/2 mouse connectors 1 X Audio port (Line Out/Line In/Mic In) 1 X RJ-45 port 1 X HDMI port(s) 1 X D-Sub (VGA) port(s) 1 X USB3.1 Gen1 port(s) 4 X USB2.0 port(s) 1x DC-In connector 1 X 4-pin CPU_FAN connector with smart fan 1 X 4-pin SYS_FAN connector with smart fan 1 X Front Panel MIC/Speaker out header 1 X Front Panel switch/LED header 1 X USB 2.0 header (Support additional 2 USB ports) 2 X SATA II 3Gb/s connector(s) 1 X CLR_CMOS header 2 X Serial port header (COM) 1 X Parallel port header (LPT) 1 X LVDS connector (optional)
CONNECTORS & HEADERS	AMI BIOS with 8 MB SPI Flash ROM Supports ACPI 5.0 & DMI Dual Display Plug and Play, STR (S3) / STD (S4) , Hardware monitor, Multi Boot Multi-Language BIOS Audio, LAN, can be disabled in BIOS Dual-Monitor function
SYSTEM BIOS	Mini ITX Form Factor 170*170
FORM FACTOR	Windows 7 64-bit Windows 8.1 32-bit
OS Support	Windows 8.1 64-bit Windows 10 64-bit Windows 10 32-bit CE/FCC Certification ErP/EuP Certification
Certifications	WHQL Certification WHCK Certification