



269.00 EUR

incl. 19% VAT, plus [shipping](#)

- J1900 BayTrail !
- 1x COM !
- 1x Parallel Port !
- MiniITX !

- Intel® Bay Trail J1900 2.0GHz/QC Core MCP Processor (Turbo 2.42GHz)
- 1\* DDR3L 1333MHz up to 8GB
- 2\* Realtek® RTL8119I GbE
- 1\* SATAII, 1\*M.2 (M-key)
- 1\* VGA, 1\* HDMI, 1\* LVDS
- 1\* RS232/422/485, 5\* RS232, 1\*USB3.0, 7\* USB2.0, 1\* Parallel
- 1\* Mini PCIe Support WIFI/BT/4G Module
- 1\* M.2 M-key (2242/2280) support SSD
- 12V DC-in
- Mini ITX Form Factor (170 x 170 mm)

Model	- JLI1N-0L
Form Factor	- ITX ( 170 * 170mm)
Processor System	- Intel® Bay Trail J1900 2.0GHz/QC, 10W, Core MCP Processor (Turbo 2.42GHz) - AMI 32M Flash ROM BIOS
Memory	- 1* DDR3L 1333MHz SO-DIMM up to 8GB
Storage	- 1* SATAII (3.0Gb/s) - 1* M.2 M-key (2242/2280, SATA interface)
Expansion	- 1* Full size Mini PCIe - 1* PCIe x1 - 1* SIM card slot

Ethernet	– 2* Realtek RTL8119I GbE
Graphics	– Intel® Z3700 Graphics, shared memory – 1* HDMI 1.4 (Max Resolution: 2560x1600@60Hz) – 1* LVDS (Max Resolution: 2560x1600@60Hz) – 1* VGA (Max Resolution: 1920x1080@60Hz) – Support Dual Displays
Audio	– USB Audio, 3W Amplifier
Watchdog Timer	– From Super I/O to drag RESETCON# – 256 segments (10sec ~ 255min)
Internal I/O	– 4* USB2.0 – 1* RS232/422/485 – 4* RS232 – 1* SATAII – 1* SATA power – 1* M.2 (M-key, 2242/2280) – 1* Full size Mini PCIe – 1* GPIO (16bit, 5V, Co-lay Parallel) – 1* PCIe x1 – 1* SIM card slot – 1* AT mode – 1* Case Open – 1* FP_Audio Header – 2* 3W Amplifier – 1* CPU FAN
External I/O	– 1* VGA – 2* RJ45 – 1* USB3.0 – 3* USB2.0 – 1* RS232 – 1* Parallel (Co-lay GPIO) – Line-out – 12V DC-in
Power	DC-in 12V – AT: Directly PWR on as Power input ready – ATX: Press Button to PWR on after Power input ready
Compliance	– CE, FCC, RoHS, REACH
Temperature	– Operating: 0°C ~ 60°C – Storage: -20°C ~ 70°C – Humidity: 10% ~ 90% RH @40°C (non-condensing)
OS Support	– Windows 7 / 8 /10, Linux