



798.00 EUR
incl. 19% VAT, plus [shipping](#)

- Intel Elkhart Lake SoC !
- 2x LAN !
- 6x USB !
- HAILO-8 Card !

- Intel Elkhart Lake SoC Processor
- 1* DDR4 3200MHz SO-DIMM up to 32GB
- 6* USB, 2* RJ45, 1* Audio (MIC + Line-out), 1* Line-IN, 3* DP, 2*COM, 1* GPIO
- Support TPM2.0
- 160.2*106*43.5 mm
- Hailo-8 M.2 M key module inside, up to 26 TOPS
- DC12V_60W Adapter

| | | |
|----------------|--|--|
| Model | - HB368F21-6412-AI (EMMC,TPM) | |
| CPU/Chipset | - Intel® Elkhart Lake SoC Processor (J6412 , TDP 10W) | |
| BIOS | - AMI Flash ROM | |
| Memory | - 1* DDR4 3200MHz SO-DIMM up to 32GB | |
| Network | - 2* Realtek RTL8119I GbE | |
| Graphics | - Intel® HD Graphics, shared memory - 3* DP (Max Resolution: 4096x2160@60Hz) , Support Triple Displays | |
| Storage | - 64GB eMMC onboard | |
| Expansion | - 1* M.2 E-key (2230, PCIe Gen.3 x1/USB2.0 interface) - 1* M.2 B-key (3042,USB3.0 interface) | |
| AI Accelerator | - 1* Hailo-8 M.2 M KEY module inside - 26 TOPS | |
| Rear Panel I/O | - 2* RJ45 - 2* USB3.1(Gen.2) - 1* USB2.0 - 1* 8 bit GPIO (Phoenix Connector 2*9 PIN) - 2* RS232/422/485 (Phoenix Connector 2*9 PIN) - 1* DC in (Lockable) | |

| | |
|--------------------|--|
| Front Panel I/O | <ul style="list-style-type: none"> - 1* Power button + Power LED - 4* USB2.0 - 1* Audio(Line out+MIC) - 1* Line in - 3* DP |
| Internal Connector | <ul style="list-style-type: none"> - SIM Card Holder |
| Power Source | <ul style="list-style-type: none"> - Adapter : AC 90~240V input / DC12V_60W output - MB : DC12~36V input |
| Compliance | <ul style="list-style-type: none"> - CE, FCC, LVD, RoHS, ErP |
| Dimensions | <ul style="list-style-type: none"> - System: 160.2 (W) x 106 (D) x 43.5 (H) mm - Box: 250 (W) x 118 (D) x 295 (H) mm - Net Weight: 1.01KG - Gross Weight: 1.52KG |
| Temperature | <ul style="list-style-type: none"> - Operating Temperature: -20 ~ 70° C - Storage Temperature: -40 ~ 85° C - Humidity: 10% ~ 95% RH @40°C (non-condensing) |
| OS Support | <ul style="list-style-type: none"> - Windows 11, Linux |