

0.00 EUR

incl. 19% VAT, plus [shipping](#)

- Intel Atom N150 !
- DDR5 bis 32GB !
- 2x Gigabit LAN !
- -20 bis 60°C !

- Intel® Atom® N150 Processor from the N-series (Formerly Twin Lake)
- High-Performance Memory: Supports DDR5 SO-DIMM, up to 32GB
- Dual Display Support: 1 x HDMI® for 4K display and 1 x LVDS Co-layout with eDP
- Storage & Expansion: 1 x M.2 E-Key, 1 x M.2 M-Key
- Comprehensive I/O: 2 x USB 3.2 Gen2, 4 x USB 2.0, 2 x RS-232/422/485
- Enhanced Security: Supports Intel fTPM
- Wide Operating Temperature: from -20 ~ 60°C for different industrial applications
- Dual LAN: 2 x RJ45 for Realtek® RTL8111H GbE

SYSTEM**MB FORM FACTOR****CPU****CHIPSET****MEMORY****BIOS****WAKE ON LAN****WATCHDOG TIMER****SECURITY****RTC BATTERY****DIMENSION (W X D)****OS SUPPORT****POWER****POWER REQUIREMENT****POWER ON MODE****CONNECTOR****DISPLAY****GPU****LVDS****HDMI®****MULTIPLE DISPLAY****AUDIO****CODEC****COMBO****LAN****ETHERNET****USB PORT****USB****Pico-ITX**

Onboard Intel® Atom® N150 Processor (Formerly Twin Lake, TDP 6W)

Intel® SoC

1 x DDR5 4800MT/s, Single Channel SO-DIMM, up to 32GB

UEFI

Yes

255 Levels

Intel® PTT (Integrated fTPM)

Lithium Battery

100.0 (W) x 72.0 (D) mm (3.9" x 2.8")

Windows® 11 (64bit)

Linux

DC-in 12V

AT / ATX (Default) Mode

DC Jack

Internal 2-pin Header

Intel® Graphics

1 x 24-bit Dual Channel LVDS (Max. Resolution: 1920 x 1200 @60Hz, co-layout eDP)

1 x HDMI® 1.4b (Max Resolution: 3840 x 2160@30Hz)

Support 2 Displays

Realtek Audio Codec

1 x Internal Header

2 x RJ45 for Realtek® RTL8111H GbE

2 x USB 3.2 Gen 2x1 (10Gbps, Formerly USB 3.1 Gen 2)

Internal Header for 4 x USB 2.0

SERIAL PORT	
COM	Internal Header for 2 x RS-232/422/485
INTERNAL I/O	
GPIO	8-Bit
SMBUS	Yes
	HDD Active LED
	Power LED
FRONT PANEL	Power On/Off
	Reset
ADDITIONAL	1 x AT/ATX Mode Selection
EXPANSION	
M.2	1 x M-Key 2280 (PCIe Gen 3 x2/SATA interface) support NVMe 1 x E-Key 2230 (USB 2.0/PCIe x1) for WIFI/BT Module
ENVIRONMENT & CERTIFICATION	
OPERATING TEMPERATURE	-20°C ~ 60°C (-4°F ~ 140°F)
STORAGE TEMPERATURE	-20°C ~ 85°C (-4°F ~ 185°F)
OPERATING HUMIDITY	10 ~ 90% relative humidity, non-condensing
CERTIFICATION	CE/FCC Class A