



698.00 EUR

incl. 19% VAT, plus [shipping](#)

- Audio speakers !
- Auto-PowerOn !
- 1024x768 ! HDMI !
- 1000 nits !

**New !** With special sunlight readable transfective TFT and high contrast (700:1) and Anti-Glare surface !

Using transfective panels and Anti-Glare touchscreens enables readability even under direct sunlight. For the first time with midrange-models, TFT panels with transfective technology are used. An anti-reflexion-coating additionally minimizes reflections on the surface. Transfective TFTs combine the advantages of reflexiv and transmissive display systems. The incoming light, which is making the surface of other display types to be unreadable, is reflected by the rear side of the panel. Because of this passive relexion the image is winning on brilliance. During dark light conditions the readability is still ensured by a transmissive backlight.

**New :** LED-Backlight-Technology, with optimized color saturation enabling particular high and shining display. The scale of displayable color nuances is increased by 45% because of the new technology. Conventional LCDs are based on CCFL backlight, which can display approx. 72% of the standard color scale of NTSC (National Television Systems Committee). With LED-Backlight-Technology 104% of the NTSC-color scale can be displayed. This results in displaying in a highly realistic manner.

The new CTFHD-1210-S TFT-Display is equipped with a 12.1" TFT panel and comes with many nice features. In any case it is the ideal display- and input-unit for your Laptop, CarPC or HTPC. Because of the 4:3 aspect ratio and the size of 12.1", the display is perfectly suitable for beeing used in POS-section or on boats. With the touchscreen functionality you easily can control your PC. The brilliant HDMI-display ensures a maximum readability and sharpness.

The device has among other features integrated Stereo-speakers and an rear camera input.

AC-Adapter for home usage and a car cigarette lighter adapter is included as well as the IR-remote-control unit and the extra long (2,5 meters) All-In-One connector cable.

The CTFHD-1210-S can be used with any PC/MAC with HDMI- and USB port.

Driver-CD included, compatible with :  
- Windows 95/98/ME/NT4/2000/XP/7/8/8.1/10

- XP Tablet PC Edition
- Windows CE 2.12, 3.0, .net
- Linux RedHat, Mandrake, ...
- Macintosh OS 9.x, 10.x
- DOS, ...

| <b>Spezifikationen</b> |   |
|------------------------|---|
| Screen size            | 12.1" digital   |
| Touchscreen            | Resistive (also available without Touchscreen or with capacitive Multi-Touchscreen) |
| Aspect Ratio           | 4:3 wide TFT screen   |
| Dot Resolution         | 3072x768= 2,359,296 dots  |
| Physical Resolution    | 1024x768  |
| Viewing angle          | 80° (T/B/L/R)   |
| Supported Resolutions  | 640x480-1920x1200   |
| Color configuration    | RGB stripe  |
| Power input            | DC 12/24VDC   |
| Power consumption      | max. 15W  |
| Video system           | 3x Video inputs (PAL/NTSC)<br>1x HDMI input   |
| Dimensions             | Display Case : 303mm x 223mm x 40mm<br>Display : 246mm x 185mm                      |
| Video input signal     | 1.0Vp-p, composite video  |
| Brightness             | 1000 cd/m <sup>2</sup>  |
| Contrast               | 700:1   |
| Vibration              | IEC68-2-6   |
| Operating Temperature  | -30° bis 80°C   |
| Automotive             | ECE R10 Electromagnetic compatibility (E13 10R-0514061)                             |
| Certifications         | ECE R118 Fire resistance (R24 118R11-020091)  |
| Features               | Full function OSD control (englisch)  |
|                        | Built-in Stereo-speakers  |
|                        | VESA compliant mounting holes (75mm)  |
|                        | Auto Power On/Off   |
|                        | Automatic switching to rear camera (by a 12V cable)                                 |
|                        |   |
| What is included ?     | - 12.1" HDMI Touchscreen TFT with Video/Audio-support                               |
|                        | - Infrared Remote Control   |
|                        | - Car dash VESA mounting bracket  |
|                        | - Touchscreen pencil  |
|                        | - HDMI/Video/Audio/Touchscreen-cable (all-in-one !) 2,5 meters length               |
|                        | - Power Adapter f. EU 230V  |
|                        | - Cigarette Lighter Adapter   |
|                        | - Touchscreen Driver-CD   |
|                        | - Manual  |



Sunlight-readable-test with CTF700-SH in Death Valley (USA)